



RÉFÉRENCE	LARGEUR (MM)	VOLUME DÔME (L)	HAUTEUR DÔME (MM)	HAUTEUR PROFONDEUR (MM)	POIDS (KG)
<b>GRV EN LAME D'USURE EN 150 X 16 MM EN 450 HB</b>					
GRV15024510..	2 450	1 500	308	H = 970 / P = 990	515
GRV20024510..	2 450	2 000	345	H = 1060 / P = 1150	607
GRV25024510..	2 450	2 500	380	H = 1200 / P = 1330	707
GRV30025010..	2 500	3 000	420	H = 1240 / P = 1490	788
GRV35024510..	2 450	3 500	459	H = 1330 / P = 1730	900
GRV40024510..	2 450	4 000	492	H = 1420 / P = 1870	945
<b>GRV EN DOUBLE LAME BOULONNÉE 150 X 20 MM EN 500 HB317</b>					
GRV15024520..	2 450	1 500	308	H = 970 / P = 990	565
GRV20024520..	2 450	2 000	345	H = 1 060 / P = 1 150	657
GRV25024520..	2 450	2 500	380	H = 1 200 / P = 1 330	757
GRV30025020..	2 500	3 000	420	H = 1 240 / P = 1 490	842
GRV35024520..	2 450	3 500	459	H = 1 330 / P = 1 730	950
GRV40024520..	2 450	4 000	492	H = 1 420 / P = 1 870	995
GRV50024520..	2 450	5 000	571	H = 1 620 / P = 2 150	1 705
GRV60024520..	2 450	6 000	604	H = 1 830 / P = 2 350	1 825
Coque acier épaisseur 10 mm et flancs acier épaisseur 8 mm					
Accrochage soudé					